
Phone: +44 130 677 0855 Email: info@noisemeters.com

Vehicle Noise Measurement with Logging, Integrating Meter



Features

- Kit includes everything needed
- Automatically calculates averages
- Data logging, integrating sound level meter
- Operation by one person

Applications

- Vehicle exhaust noise measurement
- ISO 5130 noise assessments
- Roadside, test station and motor sport venues
- Stationary vehicle sound tests
- Car, light truck and motorcycle noise levels
- Meter can be used for many other applications

Overview

The VK162B and VK162B Vehicle Noise Measurements Kits include everything you need to make sound level checks on car, motorcycle and truck exhausts. As the kit is designed specifically for vehicle noise measurement, the sound level meter has a mode that takes the average from three measurements as required by ISO 5130 similar standards. This version of the kit includes a data logging, integrating sound level meter and software.

Single Person Operation

As the kit includes a microphone extension cable and remote measurement button, the processes of setting up the microphone and making the measurements can be done by a single person. The operator can sit in the vehicle controlling the engine speed while starting the measurement and averaging process at the same time.

Vehicle Noise Kit Contents

The standard VNK162B and VNK162B Vehicle Noise Kits include the following parts:

- CR162B or CR161B Optimus Sound Level Meter
- Microphone extension cable
- Remote measurement start button
- Measurement distance and angle template
- Sound Level Calibrator
- User manual and quick start guide
- NoiseTools Software

NoiseMeters

Vehicle Noise Measurement with Logging, Integrating Meter

Specifications

Sound Level Meter

Standards IEC 61672-1 Class 1 or Class

2

ANSI S1.4 and ANSI S1.43

Type 1 or Type 2

Measurement 20 to 140 dB RMS

Range

Noise Floor Class 1 < 18 dB(A), Class 2 <

21 dB(A)

Weight 300g, 10 oz

Power 4 x AA Alkaline for typically

12 hours operation

Memory 8GB

Time History 10ms, 62.5ms, 100ms,

125ms, 250ms, 1/2 sec, 1 sec

or 2 sec

Voice Tag Up to 30 seconds of audio

notes with each measurement

Integrators EU, OSHA HC & OSHA NC,

OSHA HC & ACGIH, MSHA HC & MSHA EC, Custom

For more detailed specifications of the hand-

held sound level meter please visit the Optimus CR162B / CR161B integrating

sound level meter page.

Sound Level Calibrator

Standards IEC 60942 Class 1 or Class 2

ANSI S1.40 Class 1 or Class

2

Sound Level 94.0dB ± 0.2dB Frequency 1 kHz ± 1%

Distortion < 2%

Power 1 x 9v (PP3, 6LR61, 6F22 For more detailed information please visit the Class 1 Calibrator or Class 2 Calibrator page.

Head Office

NoiseMeters Ltd 7 Jayes Park Ockley Surrey RH5 5RR

Telephone **+44 130 677 0855** Fax **+44 845 680 0316**

Email: info@noisemeters.com Support: support@noisemeters.com

Web Sites

Main site:

https://www.noisemeters.asia

Product shortcut:

https://www.noisemeters.asia/p/vnk162b/

Tech Support:

https://support.noisemeters.com