NoiseMeters

LiveNoise LN2-IND with Industrial Noise Sign

Features

- Wall Mounted Industrial Noise Display
- Monitors Sound Levels
- Network Connection (WiFi or wired Ethernet)
- Lights up when noise levels are too high
- IEC 61672 Class 2, ANSI S1.4 Type 2
- No contract or annual fees

Applications

- Industrial Environments
- Factory Noise
- Hearing Protection

Overview

The industrial noise warning sign and interface module can be mounted on a wall or other suitable surface. An optional adjustable VESA mount can be used for more secure or corner mounting if needed. It measures the sound levels in line with the noise measurement standards, stores the results, and sends them to our cloud server.

Live Noise and Reporting

You can view the live sound level at each noise monitor or you can view long-term reports over daily, weekly, monthly or custom periods. This is all done from your web browser after logging in to your LiveNoise account.



NoiseMeters

LiveNoise LN2-IND with Industrial Noise Sign

Specifications

Technical Specifications		Dimensions
Acoustic Standards	IEC 61672-2:2002 Class 2	
	ANSI S1.4 Type 2	
Frequency Range	20 Hz to 20 kHz	
Measuring Range	30 to 120 dB	
Deviation	± 0.5 dB	
Frequency Weighting	"A" and "C"	
Noise	Leq, Fast and Slow sound	
Measurements	Level	
Additional Outputs	0-10 V or 4-20 mA	
USB Port	For USB memory stick configuration	
Ethernet Port	RJ45 socket	
Internal Memory	16 GB for up to 3 years storage	
Wembry	Storage	
Dimensions Noise	265 x 205 x 46 mm, 10.4" x	
Warning Sign	8" x 1.8"	
LiveNoise	70 x 88 x 29 mm, 2.8" x 3.5"	
Terminal Power	x 1.2" 5 VDC, max 12W (power	
	adapter included)	

Head Office

NoiseMeters Ltd 7 Jayes Park Ockley Surrey RH5 5RR

Telephone **+44 130 677 0855** Fax **+44 845 680 0316**

Email: info@noisemeters.com Support: support@noisemeters.com

Web Sites

Main site: https://www.noisemeters.asia

Product shortcut: https://www.noisemeters.asia/product/livenoise/Int-ind/

Tech Support: https://support.noisemeters.com